



FEATURES

Max absorbed power: 75 W
Air flow (max): 400 m³/h
Max air speed: 5,8 m/s
Max power noise level: 63 dB (A)
Water tank capacity: 3,5 l
Practical wheels
Horizontal swing air flow
Remote control
Timer 1-2-4 h
Handle
3 power setting
Multifunction control panel
Antidust filter




COMPACTNESS

Compact, space-saving design.



REMOTE CONTROL



FILTER

Washable fabric Antidust filter.



SILENT SYSTEM

		PELER 4E
Product code		99429
EAN code		8021183994292
Power supply	V/ph/Hz	220-240 / 1 / 50 - 60
Maximum power absorption	W	75
Stand-by power consumption	W	0,5
Fan speeds	n	3
Air volume (maximum)	m³/h	400
Air speed (maximum)	m/s	5,8
Sound pressure level (1)	dB (A)	36 / 48
Maximum Sound power level (1)	dB (A)	 63
Degrees of protection provided by enclosures		-
Insulation class		II
Power cable	n / mm²	2 x 0,75
Water tank capacity	l	3,5
Evaporative sheet		honeycomb
Control panel		touch
Maximum remote control range (distance / angle)	m / °	-
Conformity Mark		CE
Certification Mark		TUV
Product size (W x H x D)	mm	240x610x300
Gift box size (W x H x D)	mm	295x610x325
Weight (without packing)	kg	4,5
Weight (with packing)	kg	5,5
Units per master box	n	-
Master size (W x H x D)	mm	-
Timer		1, 2 or 4 hours
Removable water tank		✓
Oscillating function		✓
Remote controller		✓
Ionizer		-
Wall support		-
Power supply cable housing		-

(1) Test condition: The sound pressure level is measured in half-anechoic room far 2 meters from the front of the appliance with the microphone at 1 meter of height.
During the test, all the appliance functions are enabled with the exception of swing function (if available)