

STOVY

Catalytic stoves from 2900W

Cod. 99383

Cod. 99382



MADE IN ITALY

Guaranteed quality and safety.



DOUBLE SAFETY

Double safety system thanks to the atmosphere analyzer that automatically turns off the heater if the carbon dioxide level in the air reaches 1,5% and cuts off the gas flow in case of accidental switch off of the heater.



IMQ MARK

The IMQ mark is issued by the Italian Quality Mark Institute and guarantees conformity with the safety requirements of a product and of the materials it is made of.

FEATURES

- Max thermal output: 2900 W
- 3 power settings (2000 - 2400 - 2900 W)
- Fuel: LPG
- Crossflow fan: Stovy Turbo Thermo has a crossflow fan which allows faster and more uniform heating
- Enamelled steel body
- Space for 15 kg cylinder
- IMQ mark
- Pressure regulator
- Valve tap
- Gas hose and pressure regulator included
- Max room volume: 140 m³

Technical specifications stoves

		STOVY	STOVY TURBO THERMO
PRODUCT CODE		99383	99382
EAN CODE		8021183993837	8021183993820
Power supply		GPL	GPL
Gas supply pressure	mbar	28 / 30-37	28 / 30-37
Nominal thermal flow - Pn (max-med-min)	kW	2,9 - 2,4 - 2	2,9 - 2,4 - 2
Rated consumption (max-med-min)	g / h	210 - 170 - 100	210 - 170 - 100
Heating volume (max)	m³	80	140
Dimensions (WxHxD)	mm	430 x 780 x 330	430 x 780 x 330
Gift box dimensions (WxHxD)	mm	440 x 810 x 360	440 x 810 x 360
Weight (without packaging)	kg	10,1	11,8
Weight (with packaging)	kg	11,3	13,0
Electrical power supply	V-F-Hz	-	230 - 1 - 50
Electrical heating power	W	-	1000 + 1000
Infrared Technology		-	-
Gas safety valve		✓	✓
Pressure regulator		✓	✓
Room thermostat		-	-
Steel structure		✓	✓
Pilot burner		✓	✓
Safety system with atmosphere analyser		✓	✓
Great movement wheels		✓	✓
Piezoelectric ignition		✓	✓
Wall fixing		-	-
Fan		-	✓
Indicator light		-	-

		STOVY INFRA BLACK	STOVY INFRA SILVER	STOVY INFRA BORDEAUX	STOVY INFRA TURBO THERMO
PRODUCT CODE		99387	99386	99273	99384
EAN CODE		8021183993875	8021183993868	8021183992731	8021183993844
Power supply		GPL	GPL	GPL	GPL
Gas supply pressure	mbar	28 / 30 - 37	28 / 30 - 37	28 / 30 - 37	28 / 30 - 37
Nominal thermal flow - Pn (max-med-min)	kW	4,2 - 2,8 - 1,6	4,2 - 2,8 - 1,6	4,2 - 2,8 - 1,6	4,2 - 2,8 - 1,6
Rated consumption (max-med-min)	g / h	300 - 200 - 100	300 - 200 - 100	300 - 200 - 100	300 - 200 - 100
Heating volume (min - max)	m³	100	100	100	120
Dimensions (WxHxD)	mm	430 x 780 x 330	430 x 780 x 330	430 x 780 x 330	430 x 780 x 330
Gift box dimensions (WxHxD)	mm	440 x 810 x 360	440 x 810 x 360	440 x 810 x 360	440 x 810 x 360
Weight (without packaging)	kg	10,5	10,5	10,5	14,1
Weight (with packaging)	kg	12,0	12,0	12,0	15,3
Electrical power supply	V-F-Hz	-	-	-	230 - 1 - 50
Electrical heating power	W	-	-	-	1000 + 1000
Infrared Technology		✓	✓	✓	✓
Gas safety valve		✓	✓	✓	✓
Pressure regulator		✓	✓	✓	✓
Room thermostat		-	-	-	-
Steel structure		✓	✓	✓	✓
Pilot burner		✓	✓	✓	✓
Safety system with atmosphere analyser		✓	✓	✓	✓
Great movement wheels		✓	✓	✓	✓
Piezoelectric ignition		✓	✓	✓	✓
Wall fixing		-	-	-	-
Fan		-	-	-	✓
Indicator light		-	-	-	-