


AQUARIA S1 10 P

The compact 10-litre dehumidifier

Cod. 02060



Skyrunner



DOUBLE FILTRATION

Captures the main allergens through the antidust filter and eliminates unpleasant odours thanks to the integrated activated carbon filter.



ERGONOMIC DESIGN

Easy to move thanks to the side handles and wheels, it features a super compact design for easy positioning, even in the corners of the home



DIGITAL CONTROL

The control panel allows accurate settings and timely control of the air temperature and humidity.



INTEGRATED TIMER

For 24h on/off programming

FEATURES

Dehumidification capacity: 10 l / 24h
For rooms up to 45 m³
Coolant gas: R290
Tank capacity: 2l
Noise level 40 dB
Temperature and humidity indicator
1-24h timer
Semi-transparent removable tank
Full tank alarm
Speed: low/medium/high
Dry function
Automatic defrosting device
Wheels for transportation



Technical specifications dehumidifiers

		AQUARIA S1 10 P	AQUARIA S1 12 P	AQUARIA S1 14 P	AQUARIA S1 16 P	AQUARIA S1 20 P	AQUARIA S1 24 P
PRODUCT CODE		02060	02061	02062	02063	02064	02065
EAN CODE		8021183020601	8021183020618	8021183020625	8021183020632	8021183020649	8021183020656
Dehumidification capacity (l)	l/24h	10	12	14	16	20	24
Max. power absorption in dehumidification mode (l)	W	250	264	252	262	350	360
Max. absorption in dehumidification mode (l)	A	1,4	1,5	1,4	1,5	1,7	1,8
Max. power absorption in dehumidification mode (U.L.U.)	W	270	280	290	300	370	380
Degree of protection		IPX0	IPX0	IPX0	IPX0	IPX0	IPX0
Fan speed	nr	3	3	3	3	3	3
Tank capacity	l	2	2	2	2	5	5
Air flow rate (max)	m³/h	110	120	110	120	170	180
Product dimensions (W x H x D with wheels)	mm	293 x 487 x 218	293 x 487 x 218	293 x 512 x 218	293 x 512 x 218	367 x 610 x 274	367 x 610 x 274
Gift box dimensions (WxHxD)	mm	324 x 518 x 248	324 x 518 x 248	324 x 546 x 248	324 x 546 x 248	421 x 664 x 335	421 x 664 x 335
Noise level	dB(A)	40	40	40	40	38	38
Weight (without packaging)	kg	10,2	10,2	11,0	11,0	14,6	14,6
Weight (with packaging)	kg	10,5	10,5	11,4	11,4	16,1	16,1
Coolant gas		R290	R290	R290	R290	R290	R290
GWP (Global Warming Potential)		3	3	3	3	3	3
Refrigerant gas charge	kg	0,036	0,036	0,043	0,043	0,052	0,052
Minimum floor area for installation, use and storage	m²	4	4	4	4	4	4
Plug		EU	EU	EU	EU	EU	EU
Power supply	V-F-Hz	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50
Conformity mark		CE	CE	CE	CE	CE	CE
Antidust filter		✓	✓	✓	✓	✓	✓
Carbon filter		✓	✓	✓	✓	✓	✓
HEPA filter		-	-	-	-	✓	✓
Continuous operation with hose		✓	✓	✓	✓	✓	✓
Humidity level power settings		✓	✓	✓	✓	✓	✓
Indoor humidity visualizer		✓	✓	✓	✓	✓	✓
Indoor temperature visualizer		✓	✓	✓	✓	✓	✓
Full tank alarm		✓	✓	✓	✓	✓	✓
Child lock		-	-	-	-	✓	✓
Oscillation		-	-	-	-	✓	✓
Laundry function		✓	✓	✓	✓	✓	✓
Timer		✓	✓	✓	✓	✓	✓
Defrosting device		✓	✓	✓	✓	✓	✓
Integrated wi-fi		-	-	-	-	✓	✓

LIMITS OF OPERATING CONDITIONS

Maximum operating temperature	DB 32°C	DB 32°C	DB 32°C	DB 32°C	DB 32°C	DB 32°C
Minimum operating temperature	DB 5°C	DB 5°C	DB 5°C	DB 5°C	DB 5°C	DB 5°C

(1) DB 30°C - WB 27°C (30°C-80%)
(U.L.U.) DB 32°C - WB 23°C