

AQUARIA S1 20 P

The most complete 20-litre dehumidifier

Cod. 02064



Skyrunner



TRIPLE FILTRATION WITH HEPA FILTER

In addition to the pre-filter and activated carbon filter, it is equipped with a HEPA filter effective on particles up to 0.3 microns



MOTORISED FLAPS

Enjoy the best comfort experience thanks to the air flow management function.



TOUCHSCREEN E HIDDEN DISPLAY

Touchscreen control panel with an understated style and backlit front display (can be deactivated) for immediate humidity control



INTEGRATED WI-FI

By downloading the OS Home app it is possible to manage all its functions from your smartphone, even when away from home.

FEATURES

- Dehumidification capacity: 20l / 24h
- For rooms up to 90 m³
- Coolant gas: R290
- Tank capacity: 5l
- Noise level 38 dB
- Motorised flap
- Temperature and humidity indicator
- 1-24h timer
- Semi-transparent removable tank with handle
- Speed: low/medium/high
- Dry function
- Automatic defrosting device
- Child lock
- Wheels for transportation
- Full tank alarm



Technical specifications dehumidifiers

		AQUARIA S1 10 P	AQUARIA S1 12 P	AQUARIA S1 14 P	AQUARIA S1 16 P	AQUARIA S1 20 P	AQUARIA S1 24 P
PRODUCT CODE		02060	02061	02062	02063	02064	02065
EAN CODE		8021183020601	8021183020618	8021183020625	8021183020632	8021183020649	8021183020656
Dehumidification capacity (l)	l/24h	10	12	14	16	20	24
Max. power absorption in dehumidification mode (l)	W	250	264	252	262	350	360
Max. absorption in dehumidification mode (l)	A	1,4	1,5	1,4	1,5	1,7	1,8
Max. power absorption in dehumidification mode (U.L.U.)	W	270	280	290	300	370	380
Degree of protection		IPX0	IPX0	IPX0	IPX0	IPX0	IPX0
Fan speed	nr	3	3	3	3	3	3
Tank capacity	l	2	2	2	2	5	5
Air flow rate (max)	m³/h	110	120	110	120	170	180
Product dimensions (W x H x D with wheels)	mm	293 x 487 x 218	293 x 487 x 218	293 x 512 x 218	293 x 512 x 218	367 x 610 x 274	367 x 610 x 274
Gift box dimensions (WxHxD)	mm	324 x 518 x 248	324 x 518 x 248	324 x 546 x 248	324 x 546 x 248	421 x 664 x 335	421 x 664 x 335
Noise level	dB(A)	40	40	40	40	38	38
Weight (without packaging)	kg	10,2	10,2	11,0	11,0	14,6	14,6
Weight (with packaging)	kg	10,5	10,5	11,4	11,4	16,1	16,1
Coolant gas		R290	R290	R290	R290	R290	R290
GWP (Global Warming Potential)		3	3	3	3	3	3
Refrigerant gas charge	kg	0,036	0,036	0,043	0,043	0,052	0,052
Minimum floor area for installation, use and storage	m²	4	4	4	4	4	4
Plug		EU	EU	EU	EU	EU	EU
Power supply	V-F-Hz	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50
Conformity mark		CE	CE	CE	CE	CE	CE
Antidust filter		✓	✓	✓	✓	✓	✓
Carbon filter		✓	✓	✓	✓	✓	✓
HEPA filter		-	-	-	-	✓	✓
Continuous operation with hose		✓	✓	✓	✓	✓	✓
Humidity level power settings		✓	✓	✓	✓	✓	✓
Indoor humidity visualizer		✓	✓	✓	✓	✓	✓
Indoor temperature visualizer		✓	✓	✓	✓	✓	✓
Full tank alarm		✓	✓	✓	✓	✓	✓
Child lock		-	-	-	-	✓	✓
Oscillation		-	-	-	-	✓	✓
Laundry function		✓	✓	✓	✓	✓	✓
Timer		✓	✓	✓	✓	✓	✓
Defrosting device		✓	✓	✓	✓	✓	✓
Integrated wi-fi		-	-	-	-	✓	✓

LIMITS OF OPERATING CONDITIONS

Maximum operating temperature	DB 32°C	DB 32°C	DB 32°C	DB 32°C	DB 32°C	DB 32°C
Minimum operating temperature	DB 5°C	DB 5°C	DB 5°C	DB 5°C	DB 5°C	DB 5°C

(1) DB 30°C - WB 27°C (30°C-80%)
(U.L.U.) DB 32°C - WB 23°C