

CALDO SOUL

The fan heater for customised comfort

Cod. 99202



ROTATING BASE

Automatic horizontal air flow oscillation for improved heat diffusion



TOUCHSCREEN DISPLAY

Touch control panel with an understated style, used to set the temperature and minimum and maximum power (1000-2000W).



ECO MODE

It is able to modulate the input power depending on the measured room temperature, reducing consumption and increasing comfort levels.



SECURE SYSTEM

IP21 protection against falling drops of water and automatically switches off if it falls over

FEATURES

- Needle resistance
- Max heat output: 2000W
- 2 adjustable power levels: 1000/2000W
- IP21 vertical drip protection
- Room and safety thermostat
- Overheat protection
- Anti-tip device
- Touchscreen display
- 24h timer
- Ventilation-only function
- Swing function
- Antifreeze function (when the room temperature is below 7°C)
- Eco mode to reduce consumption
- Temperature setting from 15°C to 35°C
- Practical handle
- Remote control included



Technical specifications needle resistance fan heaters

NEW

		CALDO RADIALE	CALDO POP A	CALDO POP B	CALDO RELAX	CALDO FUNKY
PRODUCT CODE		99240	99292	99291	99338	99203
EAN CODE		8021183992403	8021183992922	8021183992915	8021183993387	8021183992038
Thermal power (Max)	W	1800	2000	2000	2000	2000
Power settings		ONLY FAN / 900 / 1800	ONLY FAN / 1000 / 2000	ONLY FAN / 1000 / 2000	ONLY FAN / 1000 / 2000	ONLY FAN / 1000 / 2000
Heating volume (max)	m³	55	60	60	60	60
Dimensions (WxHxD)	mm	275 x 112 x 290	210 x 251 x 143	210 x 251 x 143	223 x 265 x 135	206 x 275 x 140
Gift box dimensions (WxHxD)	mm	313 x 140 x 312	215 x 257 x 145	215 x 257 x 145	230 x 274 x 140	208 x 277 x 150
Weight (without packaging)	kg	1,4	1,1	1,1	1,0	1,3
Weight (with packaging)	kg	1,6	1,3	1,3	1,2	1,5
Units per master	nr	8	6	6	6	6
Master dimensions (W x H x D)	mm	575 x 325 x 640	450 x 230 x 529	450 x 230 x 529	440 x 245 x 570	465 x 570 x 218
Insulation class		II	II	II	II	II
Degree of protection provided by covers		IPX0	IP21	IP21	IP21	IP21
Electrical power supply	V-F-Hz	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50/60
Conformity mark		CE	CE	CE	CE	CE
Timer		-	-	-	-	-
Room thermostat		✓	✓	✓	✓	✓
Safety thermostat		✓	✓	✓	✓	✓
Ventilation function		✓	✓	✓	✓	✓
Oscillating function		-	-	-	-	✓
Anti-tip switch		-	-	-	✓	✓
Anti-ice function		✓	-	-	✓	-
Power selector		✓	✓	✓	✓	✓
Tabletop position		✓	✓	✓	✓	✓
Wall-mounted position		-	-	-	-	-

NEW

NEW

		CALDO ROCK M	CALDO ROCK O	CALDO SOUL	CALDO TEKNO	CALDOSILENT	CALDO DUO
PRODUCT CODE		99293	99294	99202	99241	99329	99201
EAN CODE		8021183992939	8021183992946	8021183992021	8021183992410	8021183993295	8021183992014
Thermal power (Max)	W	2000	2000	2000	2000	2400	2000
Power settings		ONLY FAN / 1000 / 2000	ONLY FAN / 1000 / 2000	ONLY FAN / 1000 / 2000	ONLY FAN / 1000 / 2000	ONLY FAN / 1200 / 2400	ONLY FAN / 1000 / 2000
Heating volume (max)	m³	60	60	60	60	80	60
Dimensions (WxHxD)	mm	217 x 275 x 155	217 x 290 x 155	204 x 271 x 140	205 x 280 x 163	267 x 343 x 251	250 x 113 x 325 *
Gift box dimensions (WxHxD)	mm	225 x 280 x 160	225 x 295 x 160	205 x 275 x 140	220 x 286 x 164	285 x 360 x 265	255 x 120 x 338 *
Weight (without packaging)	kg	1,1	1,3	1,3	1,3	2,7	1,9
Weight (with packaging)	kg	1,3	1,5	1,5	1,5	3,0	2,2
Units per master	nr	6	6	6	6	3	6
Master dimensions (W x H x D)	mm	500 x 235 x 580	500 x 235 x 610	435 x 515 x 215	507 x 587 x 230	810 x 380 x 300	375 x 270 x 696
Insulation class		II	II	II	II	II	II
Degree of protection provided by covers		IP21	IP21	IP21	IP21	IP21	IP21 / IP24
Electrical power supply	V-F-Hz	220-240 - 1 - 50/60	220-240 - 1 - 50/60	220-240 - 1 - 50/60	220-240 - 1 - 50	230 - 1 - 50	230 - 1 - 50/60
Conformity mark		CE	CE	CE	CE	CE	CE
Timer		-	-	✓	✓	✓	✓
Room thermostat		✓	✓	✓	✓	✓	✓
Safety thermostat		✓	✓	✓	✓	✓	✓
Ventilation function		✓	✓	✓	✓	✓	✓
Oscillating function		-	✓	✓	-	✓	-
Anti-tip switch		✓	✓	✓	✓	✓	✓
Anti-ice function		-	-	✓	✓	✓	✓
Power selector		✓	✓	✓	✓	✓	✓
Tabletop position		✓	✓	✓	✓	✓	✓
Wall-mounted position		-	-	-	-	-	✓

* The dimensions of the Caldo Duo fan heater are indicated considering it in the standard tabletop position