


NEXYA COMMERCIAL CEILING [OS5+IS5]

Inverter mono-split air conditioners for large rooms



HIGH EFFICIENCY

High-performance R32 refrigerant gas with maximum technological efficiency, to reach the energy class A++.



FEATURES

Energy-efficient inverter technology with low-GWP R32 refrigerant gas.

Remote ON-OFF

All units in the commercial line are fitted with terminals to control the remote switching on and off of the unit via an external device.

Alarm contact

The units in the commercial line have a contact that allows the alarm status of the product to be synchronised with an external device.

Hydrophilic Aluminium coating

Suitable for installation in coastal or particularly humid areas, thanks to its excellent anti-corrosion properties. With equivalent environmental conditions, the new coating of the condensers guarantees them a longevity exceeding 7 times that of the traditional models.

FUNCTIONS

- **Cooling, heating, dehumidification and ventilation**
- **Auto, Co, Sleep, Silent and Turbo functions**
- **24h timer:** for scheduling switch on and off.
- **Swing function:** automatically regulates the air flow (horizontal and vertical)
- **Follow Me function:** precise temperature detection at the remote control location.
- **Gear function:** 3 power options (50-75-100%) to optimise energy consumption.
- **Short cut function:** to automatically return to the previous settings.
- **Anti dust filter:** to capture dust and pollen.
- **Self-Clean function:** automatically cleans and dries the evaporator eliminating dust, mould and grease to ensure clean air in the room.

				Nexya E Ceiling 24 [OS5+IS5]	
INDOOR UNIT CODE				OS-SANFH24EI	BMS
INDOOR UNIT EAN CODE				8021183119206	
OUTDOOR UNIT CODE				OS-CANCH24EI	
OUTDOOR UNIT EAN CODE				8021183119060	
Output power in cooling mode (min/rated/max)			kW	3,22/6,804/7,77	HEAT PUMPS
Output power in heating mode (min/rated/max)			kW	2,72/7,62/8,29	
Absorbed power in cooling mode (min/rated/max)			kW	0,747/2,062/2,93	
Absorbed power in heating mode (min/rated/max)			kW	0,65/2,05/2,85	
Current consumption in cooling mode (min/rated/max)			A	3,9/10,54/13,1	
Current consumption in heating mode (min/rated/max)			A	3,5/9,5/12,7	
EER				3,3	
COP				3,72	
Maximum power consumption in cooling mode			kW	3,7	
Maximum power consumption in heating mode			kW	3,7	
Energy efficiency class in cooling				A++	
Energy efficiency class in heating mode - Average season				A+	
Energy efficiency class in heating mode - Warmer season				A+++	
Energy efficiency class in heating mode - Cold season				/	
Energy consumption in cooling mode		kWh/year	kWh/year	413	FAN COIL UNITS
Annual energy consumption in heating mode - Average season		kWh/year	kWh/year	1925	
Annual energy consumption in heating mode - Warmer season		kWh/year	kWh/year	1592	
Annual energy consumption in heating mode - Cold season			kWh/year	/	
Dehumidification capacity			l/h	2,72	
DESIGN LOAD (EN 14825)	Cooling	Pdesignc	kW	7,2	
	Heating / Average	Pdesignh	kW	5,5	
	Heating / Warmer	Pdesignh	kW	5,8	
	Heating / Colder	Pdesignh	kW	/	
SEASONAL EFFICIENCY (EN14825)	Cooling	SEER		6,1	
	Heating / Average	SCOP (A)		4	
	Heating / Warmer	SCOP (W)		5,1	
	Heating / Colder	SCOP (C)		/	
INDOOR UNIT	Sound power (EN 12102)	LWA	dB(A)	55	HRV
	Sound pressure (max/med/min/silence)		dB(A)	49/46/43/-	
	Air flow rate in cooling mode (max/med/min)		m³/h	1192-1023-853	
	Air flow rate in heating mode (max/med/min)		m³/h	1192-1023-853	
	Degree of protection			/	
	Dimensions (WxHxD) (without packaging)		mm	1068x235x675	
	Weight (without packaging)		kg	28,0	
	Dimensions (WxHxD) (with packaging)		mm	1145x318x755	
	Weight (with packaging)		kg	33,1	
	Sound power (EN 12102)	LWA	dB(A)	66	
OUTDOOR UNIT	Sound pressure		dB(A)	60	UNICO
	Air flow rate (max)		m³/h	3500	
	Degree of protection			/	
	Dimensions (WxHxD) (without packaging)		mm	890x673x342	
	Weight (without packaging)		kg	43,9	
	Dimensions (WxHxD) (with packaging)		mm	995x740x398	
	Weight (with packaging)		kg	46,9	
	Connecting liquid pipeline diameter		inch - mm	3/8" - 9,52	
	Connecting gas pipeline diameter		inch - mm	5/8" - 15,9	
	Maximum piping length		m	50	
COOLING CIRCUIT	Maximum height difference		m	25	MONO AND MULTISPLIT
	Covered piping length from pre-load		m	5	
	Piping recommended minimum length		m	3	
	Refrigerant increase (over 5 m of pipes)		g/m	24	
	Maximum operating pressure		MPa	4,3-1,7	
	Refrigerant gas*	Type	Type	R32	
	Global warming potential	GWP		675	
	Refrigerant gas charge		kg	1,5	
	Supply voltage indoor unit		V/F/Hz	One Phase 220-240 / 1 / 50	
	Supply voltage outdoor unit		V/F/Hz	One Phase 220-240 / 1 / 50	
ELECTRICAL CONNECTIONS	Outdoor unit power supply connection	Pipes		3 x 2,5 mm²	PORTABLES
	Indoor - Outdoor unit connection	Pipes		4 x 1 mm²	
	Max Current		A	19	
LIMITS OF OPERATING CONDITIONS					
Indoor ambient temperature	Maximum temperature in cooling			DB 32°C	
	Minimum temperature in cooling			DB 16°C	
	Maximum temperature in heating			DB 30°C	
	Minimum temperature in heating			DB 0°C	
Outdoor ambient temperature	Maximum temperature in cooling			DB 50°C	
	Minimum temperature in cooling			-	
	Maximum temperature in heating			DB 24°C	
	Minimum temperature in heating			DB -15°C	

The declared data relate to the conditions provided for in EN 14511, EN 14825 and EU Delegated Regulation 626/2011. The actual power consumption of the product, in conditions of real use, may differ from what is indicated. The data are subject to change and modification without prior notice. Dehumidification values refer to DB 27°C WB 19°C conditions.

The sound pressure values are measured under the following conditions: in semi-anechoic chamber, unit positioned in a free space, measuring device positioned 1 metre below the internal unit and 1 metre from the front of the internal unit.

The sound pressure values of the outdoor units are measured under the following conditions: in a semi-anechoic chamber, unit positioned in free space, measuring device positioned at a distance of 1 metre (outdoor unit).

*Non-hermetically sealed equipment containing fluorinated gases with GWP equivalent of 675.

Energy efficiency classes refer to a range between A+++ and D.