PELER 25 WIFI

The ideal evaporative cooler for superior comfort.

Cod. 99209







DUAL FUNCTION: FAN /COOLER

Functions with or without water, respectively as a cooler or fan.



DIGITAL CONTROLS

Latest generation panel, for precise control over all the functions.



DRY AIR FUNCTION

Evaporative panel drying function to prevent the formation of mould and bacteria.



PLASMA FUNCTION

Constant air ionisation function (always active) for improved quality





FEATURES

Maximum power consumption: 90W Air flow rate (maximum): 1500 m³/h Air speed (maximum): 8.0 m/s

Air reach up to 13 m

Maximum sound power level: 58dB(A)

AC motor

Direct filling from tank

LED display

3 operating modes (normal, natural, sleep)

3 fan speeds (low, medium, high)

3 air intakes for enhanced air flow

Large 25-litre water tank

Purification with air filter and honeycomb evaporative panel

1-9 hour timer

Antidust filter

Automatic swing mode with 360° rotation

Water tank low-level flashing light

User-friendly remote control included

Easy to disassemble and fold (top part nests into the tank) for compact

storage when not in use

Handy wheels for transportation

Ideal for medium-sized areas (such as indoor openspaces) and outdoor

areas (such as verandas, patios)

Ice boxes included



Evaporative coolers

		NEW	NEW	NEW	NEW	NEW
		PELER 4T	PELER 7T	PELER TOWER 10	PELER 25 WIFI	PELER 40
PRODUCT CODE		99211	99210	99208	99209	99207
EAN CODE		8021183992113	8021183992106	8021183992083	8021183992090	8021183992076
Electrical power supply	V/F/Hz	220-240 /1/50 - 60	220-240 /1/50 - 60	220-240 /1/50 - 60	220-240 /1/50 - 60	220-240 /1/50 - 60
Maximum power absorption	W	60	80	38	90	120
Stand-by power consumption	W	-	0,2	0,4	0,5	0,5
Fan speed	n	3	3	24	3	3
Air flow rate (maximum)	m³/h	140	300	1000	1500	1800
Air speed (maximum)	m/s	7,2	7	6,5	8,0	7,0
Sound pressure level (1)	dB(A)	45	60	55	44	65
Maximum Sound power level (1)	dB(A)	◆ 60	◆ 60	4) 63	◆	◆ 65
Insulation class		II	II	II	II	II
Power cable	n / mm²	2 x 0,75				
Water tank capacity	I	3,8	7	10	25	40
Evaporative sheet		Honeycomb	Honeycomb	Honeycomb	Honeycomb	Honeycomb
Control panel		Touch	Touch	Digital	Digital	Touch
Conformity mark		CE	CE	CE	CE	CE
Dimensions (WxHxD)	mm	260 x 600 x 232	235 x 567 x 260	309 x 938 x 279	333 x 840 x 418	485 x 1009 x 403
Gift box dimensions (WxHxD)	mm	293 x 630 x 265	286 x 593 x 311	340 x 775 x 330	386 x 600 x 454	560 x 1090 x 490
Weight (without packaging)	kg	4,0	3,6	6,1	7,1	14,1
Weight (with packaging)	kg	5,3	4,4	8,5	10,5	18,0
Timer		√	√	√	√	√
Removable water tank		√	-	√	√	-
Oscillating function		√	√	√	√	√
Remote control		√	√	√	√	√
lonizer		-	-	-	√	-
Power off switch		-	-	-	-	-
Power supply cable housing		-	-	-	-	-

⁽¹⁾ Test conditions: the sound pressure was measured in a semi-anechoic chamber at a distance of 2 metres from the front part of the appliance with the microphone at a height of 1 metre. During measurement, all device functions are enabled except swing (if present).