PELER 7T

The air cooler featuring an essential design that's easy to use

Cod. 99210









DUAL FUNCTION: FAN /COOLER

Functions with or without water, respectively as a cooler or fan.



TOUCHSCREEN DISPLAY

Touch-screen control panel, with minimal aesthetic impact, for immediate control.



AIR FLOW AUTO-SWING

Continuous and automatic orientation of air flow from right to left



INTEGRATED TIMER

Automatic shut-down programmable up to 7 hours

FEATURES

Maximum power consumption: 80W Air flow rate (maximum): 300 m³/h Air speed (maximum): 7.0 m/s

Maximum sound power level: 60 dB(A)

Top or bottom filling (can be filled from the bottom by removing the screw on the rear grille)

LED touchscreen display

3 operating modes (normal, natural, sleep) 3 fan speeds (low, medium, high)

Large 7-litre water tank

Purification with air filter and honeycomb evaporative panel

1-7 hour timer

Antidust filter

Swing mode for horizontal air flow

Manual vertical flap adjustment

User-friendly remote control included

Super-compact design

Handy wheels for transportation

Ice boxes included



Evaporative coolers

		NEW	NEW	NEW	NEW	NEW
		PELER 4T	PELER 7T	PELER TOWER 10	PELER 25 WIFI	PELER 40
PRODUCT CODE		99211	99210	99208	99209	99207
EAN CODE		8021183992113	8021183992106	8021183992083	8021183992090	8021183992076
Electrical power supply	V/F/Hz	220-240 /1/50 - 60	220-240 /1/50 - 60	220-240 /1/50 - 60	220-240 /1/50 - 60	220-240 /1/50 - 60
Maximum power absorption	W	60	80	38	90	120
Stand-by power consumption	W	-	0,2	0,4	0,5	0,5
Fan speed	n	3	3	24	3	3
Air flow rate (maximum)	m³/h	140	300	1000	1500	1800
Air speed (maximum)	m/s	7,2	7	6,5	8,0	7,0
Sound pressure level (1)	dB(A)	45	60	55	44	65
Maximum Sound power level (1)	dB(A)	◆) 60	◆》 60	◆) 63	◆》 58	● 65
Insulation class		II	II	II	II	II
Power cable	n / mm²	2 x 0,75				
Water tank capacity	I	3,8	7	10	25	40
Evaporative sheet		Honeycomb	Honeycomb	Honeycomb	Honeycomb	Honeycomb
Control panel		Touch	Touch	Digital	Digital	Touch
Conformity mark		CE	CE	CE	CE	CE
Dimensions (WxHxD)	mm	260 x 600 x 232	235 x 567 x 260	309 x 938 x 279	333 x 840 x 418	485 x 1009 x 403
Gift box dimensions (WxHxD)	mm	293 x 630 x 265	286 x 593 x 311	340 x 775 x 330	386 x 600 x 454	560 x 1090 x 490
Weight (without packaging)	kg	4,0	3,6	6,1	7,1	14,1
Weight (with packaging)	kg	5,3	4,4	8,5	10,5	18,0
Timer		√	√	√	√	√
Removable water tank		√	-	√	√	-
Oscillating function		√	√	√	√	√
Remote control		√	√	V	√	V
lonizer		-	-	-	V	-
Power off switch		-	-	-	-	-
Power supply cable housing		-	-	-	-	-

⁽¹⁾ Test conditions: the sound pressure was measured in a semi-anechoic chamber at a distance of 2 metres from the front part of the appliance with the microphone at a height of 1 metre. During measurement, all device functions are enabled except swing (if present).