

SECCOPROF

Professional dehumidifiers for large spaces

Cod. 02106

Cod. 02107



SUPER POWER

Seccoprof is able to absorb up to 40 litres of excess humidity per day, thus allowing the dehumidification of large spaces.



NON-STOP OPERATING

Continuous condensation drain for non-stop dehumidification, without needing to remove the tank.



WARM GAS DEFROSTING

Guarantees constant operation of the compressor, avoiding frequent activation and deactivation periods, and also allows operation at temperatures close to 0°C.



DIGITAL CONTROL

The control panel allows accurate settings and timely control of the air temperature and humidity.

FEATURES

- Dehumidification capacity: 30l / 24h and 40l / 24h
- For rooms up to 150/200 m³
- Coolant gas: R290
- Tank capacity: 8l
- Noise level 52 dB
- Temperature and humidity indicator
- 1-24h timer
- Removable tank with water level visualisation
- 2 fan speed levels
- Dry and Fan function
- Automatic defrosting device
- Wheels for transportation
- Full tank alarm
- 2 filtering levels (pre-filter / activated carbon filter)



TERMOVENTILATORI

CONVECTORS

INFRARED HEATERS

RADIATORS

DEHUMIDIFIERS

HUMIDIFIERS

AIR PURIFIER AND AROMA DIFFUSER

		SECCOPROF 30 P	SECCOPROF 40 P
PRODUCT CODE		02106	02107
EAN CODE		8021183021066	8021183021073
Dehumidification capacity (l)	l/24h	30	40
Power absorption in dehumidification mode (l)	W	580	600
Max. power absorption in dehumidification mode (U.L.U.)	W	620	750
Fan speed	nr	2	2
Tank capacity	l	8	8
Air volume (max)	m³/h	240	240
Sound pressure	dB(A)	52	52
Dimensions (WxHxD)	mm	312 x 635 x 453	312 x 635 x 453
Gift box dimensions (WxHxD)	mm	356 x 688 x 492	356 x 688 x 492
Weight (without packaging)	kg	24,9	27,2
Weight (with packaging)	kg	26,8	29,0
Refrigerant gas / Charge (kg)		R290 / 0,083	R290 / 0,096
Power supply	V-F-Hz	220-240 - 1 - 50	220-240 - 1 - 50
Plug		Schuko	Schuko
Power supply min - max	V	220-240	220-240
Antidust filter		✓	✓
Carbon filter		✓	✓
HEPA filter		-	-
Continuous operation with hose		✓	✓
Digital control		✓	✓
Humidity level power settings		✓	✓
LCD Display		✓	✓
Indoor humidity visualizer		✓	✓
Indoor temperature visualizer		✓	✓
Full tank alarm		✓	✓
Defrosting device		✓	✓
Mot gas defrosting system		✓	✓
Handle		✓	✓
Wheels		✓	✓
Tank with push-pull locking		-	-
Tank with Handle		-	-
Visible water level		✓	✓

LIMITS OF OPERATING CONDITIONS

Maximum operating temperature	DB 35°C
Minimum operating temperature	DB 2°C

(l) DB 32°C - WB 29°C (32°C-80%)
(U.L.U.) DB 35°C - WB 31°C (35°C-80%)